



### STYLEGUARD-DTV

**Diamond-to-View** square is a strong tubular railing system manufactured in accordance with BSEN 1722 part 9. Supplied with a mitred, flat top or complemented with a range of forged-head finials.

Standard sizes					
Fence height mtrs	Panel width	Square 25 x 25 SHS (mm)	Centres	Channel	Posts
1.0	2720	2	130	50 x 25	50 x 50 x 3
1.2	2720	2	130	50 x 25	50 x 50 x 3
1.5	2720	2	130	50 x 25	50 x 50 x 3
1.8	2720	2.5	130	50 x 25	70 x 70 x 3
2.0	2720	2.5	130	50 x 25	80 x 80 x 3
2.4	2720	2.5	130	50 x 25	80 x 80 x 3

*Heights above 2.4m are available on request.*

#### Heights

Verticals can be in any height up to 3.0m and produced from square hollow section, square-to-view or diamond-to-view with either blunt or pointed tops.

#### Horizontals

Available in flat, rolled steel channel section.

#### Posts

Intermediates, Corners and Ends are available in a wide range of sizes and materials including: RHS and RSJ,

with the provision to be stepped or cranked to suit site conditions, secured in concrete (supplied complete with two support legs per standard panel for concrete-in fixing) or base plated for surface mounting. All RHS and RSJ posts are manufactured with welded steel caps and a range of post head details are available for all railings as an optional extra.

#### Panels

Panels are available as standard to 2.72m wide panels welded in

accordance with BS 1722 Pt9. Panels can also be made to suit your specific requirements - straight, curved or raked.

#### Gates

Standard gates are available or tailored-made to suit your requirements. All gates are supplied with side hung adjustable hinges, pad-lockable drop-bolts, multi-holed to suit site conditions and robust pad-lockable slide latches. See page 34 for further details.

### STYLEGUARD-R

**Round** tubular railings manufactured in accordance with BSEN 1722 part 9. Supplied with a mitred or flat top or complemented with a range of forged-head finials.

Standard sizes					
Fence height mtrs	Panel width	Tubular 25 dia CHS (mm)	Centres	Rails	Posts
1.0	2720	2	130	50 x 25	50 x 50 x 3
1.2	2720	2	130	50 x 25	50 x 50 x 3
1.5	2720	2	130	50 x 25	50 x 50 x 3
1.8	2720	2.5	130	50 x 25	70 x 70 x 3
2.0	2720	2.5	130	50 x 25	80 x 80 x 3
2.4	2720	2.5	130	50 x 25	80 x 80 x 3

*Heights above 2.4m are available on request.*

#### Heights

Verticals can be in any height up to 2.4m and produced from hollow tube, round with either blunt or pointed tops.

#### Horizontals

Available in flat, rolled steel channel section.

#### Posts

Intermediates, Corners and Ends are available in a wide range of sizes and materials including: RHS, CHS and RSJ, with the provision to be stepped

or cranked to suit site conditions, secured in concrete (supplied complete with two support legs per standard panel for concrete-in fixing) or base plated for surface mounting. All RHS & CHS posts are supplied with welded steel caps. A range of post head details available for all railings as an optional extra.

#### Panels

Panels are available as standard to 2.72m wide panels welded in accordance with BS 1722 Pt9.

Panels can also be made to suit your specific requirements - straight, curved or raked.

#### Gates

Standard gates are available or tailored-made to suit your requirements. All gates are supplied with side hung adjustable hinges, pad-lockable drop-bolts, multi-holed to suit site conditions and robust pad-lockable slide latches. See page 34 for further details.