



STYLEGUARD-BT

Bow top railing systems are available in a variety of styles: single, interlaced, bow in bow, bar in bow and bow and bar.

AVAILABLE FROM STOCK SEE PAGE 4

Standard sizes

Fence height mtrs	Embedded length of post	Diameter of vertical round (mm)	Spacing of verticals (centres)	Size of horizontals mm	Size of RSJ post	Size of RHS post
1.0	450	12	112	30 x 10	100 x 55	50 x 50 x 3
1.2	550	12	112	30 x 10	100 x 55	50 x 50 x 3
1.2	550	16	112	40 x 10	100 x 55	50 x 50 x 3
1.5	550	16	112	40 x 10	100 x 55	50 x 50 x 3
1.8	600	20	131	50 x 10	100 x 55	70 x 70 x 3
2.4	600	22	145	50 x 10	100 x 55	80 x 80 x 3

Heights

Produced from solid bar, in all heights up to 3.0m.

Horizontals

Available in flat or channel section.

Posts

Intermediates, Corners and Ends are available in a wide range of sizes and materials including: RHS and RSJ, with the provision to be stepped or cranked to suit site conditions, secured in concrete (supplied complete with two support legs

per standard panel for concrete-in fixing) or base plated for surface mounting.

All posts are manufactured with welded steel caps and a range of post head details are available for all railings as an optional extra.

Panels

Panels are available as standard to 2.72m wide panels welded in accordance with BS 1722 Pt9. Panels can also be made to suit your specific requirements - custom lengths, straight, curved or raked.

Gates

Standard gates are available or tailored-made to suit your requirements. All gates are supplied with adjustable hinges, pad-lockable drop-bolts, multi-holed to suit site conditions and robust pad-lockable slide latches.

See page 34 for further details.

PLAYSAFE-BT

Designed with safety in mind and available in a range of more than 180 colours, PLAYSAFE complements a stimulating environment with additional safety and security .

Barkers PLAYSAFE Bow Top has been designed with safety in mind. PLAYSAFE meets the requirements of BS EN 1176 playground equipment, with gaps not exceeding 89mm and free from any neck entrapments.

Heights

Produced from solid bar in all heights up to 2.4m.

Horizontals

Available in flat or channel section.

Posts

Intermediates, Corners and Ends are available in a wide range of sizes and materials including: RHS and RSJ, with the provision to be stepped or cranked to suit site conditions, secured in concrete (supplied complete with

two support legs per standard panel for concrete-in fixing) or base plated for surface mounting. All posts come with welded steel caps. A range of post head details available for all railings as an optional extra.

Panels

Panels are available as standard to 2.72m wide panels welded in accordance with BS 1722 Pt9. Panels can also be made to suit your specific requirements - straight or curved.

Gates

Standard gates are available or tailored-made to suit your requirements. All gates are supplied with adjustable hinges, pad-lockable drop-bolts, multi-holed to suit site conditions and robust pad-lockable slide latches.

HydraClose gates are particularly suited for use with PlaySafe-BT. See page 35 for further details.